



WI-FI IP КАМЕРА С PAN/TILT



ТЕХНИЧЕСКА СПЕЦИФИКАЦИЯ

System

Operation system

Embedded Linux OS

Online visitor

Support 4 visitors at the same time

Image Capture	Image sensor	1/4 inch 720p Progressive Scan CMOS
	Minimum Illumination	0.3~0.5Lux~Color mode~,0Lux~B&W mode~
	Lens	4.0mm@F2.1
	View Angle	71.1°~diagonal~
	Night vision	Dual Filter,IR-Cut~12pcs 850nm Φ5mm~IR L IR irradiation distance:5~10m
Video	Encode format	H.264 main profile@level:4.0/Motion-JPEG/JPEG
	Three Stream	Main Stream:720p(1280X720)@25fps Sub Stream:360p(640X360)@25fps Third Stream:180p(320X180)@10fps
	Bit Rate	128~4096kbps
	Maximum frame rate	25fps
	Image adjustment	Contrast~Brightness~Saturation~Hue
Audio	Input	Built-in -48 dB microphone
	Output	Built-in speaker(8Ω1W)
	Sampling frequency / width	8KHz/16bit
	Compression standard	ADPCM/32kbps
Network	Ethernet	10Base-T / 100Base-TX, RJ45 connector
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP, etc

Wireless LAN	IEEE802.11b/g/n	
Wireless LAN Frequency	2.4~ 2.4835GHz	
Wireless LAN security	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption	
Pan-tilt	Pan-tilt	Pan□355°, tilt□120°
	Preset position	PC APP□support 16 positions, phone: APP:support 5 positions
Memory	Socket	TF Push-push socket,Maximum support 128
Alarm	Alarm Trigger	Motion detection
Physical	Rated voltage	DC 5V±5%
	Power consumption	Related power: 3.5W(IR LED on), Maximum Power: 7W(Pan&Tilt on)
	Operating condition	Temperature:-10□50°C,humidity:□90%
Environmental	Weight	Gross□688(Note: in kind prevail)
	Package size	208*154*137mm (L×W×H)

Още шпионски продукти от същата категория

Към продукта "Wi-Fi IP камера с PAN/TILT"

Copyright 2009 - 2017 Spy.bg