

# EU Declaration of Conformity

# SAMSUNG



***We hereby declare that the product***

Type of equipment : NETWORK CAMERA  
Brand Name / Trade Mark : SAMSUNG  
Model number : QNV-7080RP  
Variant Model : -

***satisfies all the technical regulations applicable to the product within the scope of Council Directives 2014/30/EU***

EN 55022:2010 : Limits and methods of measurement of radio disturbance characteristics of information technology equipment  
EN 50581:2012 : Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances  
EN 50130-4:2011+A1:2014 : Product family standard: Immunity requirements for components of fire, intruder and social alarm systems  
EN 61000-4-2:2009 : Electrostatic discharge immunity test  
EN 61000-4-3:2006+A2:2010 : Radiated, radio-frequency, electromagnetic field immunity test  
EN 61000-4-4:2012 : Electrical fast transient/burst immunity test  
EN 61000-4-5:2014 : Surge immunity test  
EN 61000-4-6:2009 : Immunity to conducted disturbances, induced by radio-frequency fields  
EN 61000-4-11:2014 : Voltage dips, short interruptions and voltage variations immunity tests

***All essential testing suites have been carried out.***

Manufacturer : Tianjin Samsung Techwin Opto-Electronic Co., Ltd.  
Manufacturer address : No.11 Weiliu Rd, Micro-Electronic Industrial Park, TEDA, Tianjin, 300385, People's Republic of China  
Telephone / Fax : 82-02-729-2900 / 82-02-729-2904 (www.hanwhatechwin.com)  
Applicant : Hanwha Techwin Co., Ltd.  
Applicant address : 1204, Changwon-daero, Seongsan-gu, Changwon-si, Gyeongsangnam-do, Korea

***This declaration is issued under the sole responsibility of the manufacturer and his authorised representative.***

Authorized signatory

Name / Title : Jei Soon, Kang / Principal Research Engineer  
Date of issue : Jul. 10, 2016




# EMC TEST REPORT For CE

Test Report No. : KES-E1-16T0342  
Date of Issue : Jul. 10, 2016  
Product name : NETWORK CAMERA  
Model/Type No. : QNV-7080RP  
Variant Model : -  
Applicant : Hanwha Techwin Co., Ltd.  
Applicant Address : 1204, Changwon-daero, Seongsan-gu, Changwon-si,  
Gyeongsangnam-do, Korea  
Manufacturer : Tianjin Samsung Techwin Opto-Electronic Co.,Ltd.  
Manufacturer Address : No.11 Weiliu Rd, Micro-Electronic Industrial Park, TEDA, Tianjin,  
300385, People's Republic of China  
Date of Receipt : Jun. 16, 2016  
Test date : Jul. 03, 2016 – Jul. 09, 2016  
Test Results :  **In Compliance**       **Not in Compliance**

*Tested by*

*Reviewed by*

\_\_\_\_\_  
Dae Hyun, Kim  
EMC Test Engineer

\_\_\_\_\_  
  
Dong-Hun, Jang  
EMC Technical Manager



**KES Co., Ltd.**

C-3701, Simin-daero 365-40,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:  
KES-E1-16T0342  
Page (2) of (79)

---

**REPORT REVISION HISTORY**

<b>Date</b>	<b>Test Report No.</b>	<b>Revision History</b>
Jul. 10, 2016	KES-E1-16T0342	Issued

***This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document Jun be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.***

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

---

## TABLE OF CONTENTS

1.0	General Product Description .....	4
1.1	Test Voltage & Frequency .....	7
1.2	Variant Model Differences.....	7
1.3	Device Modifications .....	7
1.4	Equipment Under Test.....	7
1.5	Support Equipments.....	7
1.6	External I/O Cabling.....	8
1.7	E.U.T Operating Mode(s).....	8
1.8	Configuration.....	9
1.9	Calibration Details of Equipment Used for Measurement.....	10
1.10	Test Facility .....	10
1.11	Laboratory Accreditations and Listings .....	10
2.0	Test Regulations.....	11
2.1	Conducted Emissions at Mains Power Ports.....	13
2.2	Conducted Emissions at Telecommunication Ports .....	14
2.3	Radiated Electric Field Emissions(Below 1 GHz) .....	15
2.4	Radiated Electric Field Emissions(Above 1 GHz).....	16
2.5	Harmonic Current Emissions.....	17
2.6	Voltage Fluctuations and Flicker .....	18
3.0	Criteria for compliance.....	19
3.1	Electrostatic Discharge.....	21
3.2	Radiated Electric Field Immunity .....	25
3.3	Electrical Fast Transients/Bursts .....	28
3.4	Surge Transients.....	31
3.5	Conducted Disturbance.....	34
3.6	Voltage Dips and Short Interruptions.....	36
APPENDIX A – TEST DATA.....		38
Conducted Emissions at Mains Power Ports.....		38
Conducted Emissions at Telecommunication Ports .....		40
Radiated Electric Field Emissions(Below 1 GHz) .....		44
Radiated Electric Field Emissions(Above 1 GHz).....		45
Harmonic Current Emissions and Voltage Fluctuations and Flicker .....		53
Test Setup Photos and Configuration .....		56
Conducted Voltage Emissions .....		56
Conducted Telecommunication Emissions .....		57
Radiated Electric Field Emissions(Below 1 GHz) .....		59
Radiated Electric Field Emissions(Above 1 GHz).....		61
Harmonic Current Emissions and Voltage Fluctuations and Flicker .....		63
Electrostatic Discharge .....		64
Radiated Electric Field Immunity .....		65
Electrical Fast Transients/Bursts.....		66
Surge Transients.....		67
Conducted Disturbance.....		68
Voltage Dips and Short Interruptions.....		69
EUT External Photographs.....		70
EUT Internal Photographs .....		71

## 1.0 General Product Description

### Main Specifications of E.U.T are:

<b>Video</b>	
Imaging Device	1/3" 4M CMOS
Total Pixels	2720x1536
Effective Pixels	2688x1520
Scanning System	Progressive
Min. Illumination	Color : 0.15Lux, B/W : 0Lux
<b>Lens</b>	
Focal Length (Zoom Ratio)	Motorized 2.8~12mm
Max. Aperture Ratio	F1.4
Angular Field of View	H 109.7°~26.0° / V 60.8°~15.2° / D 131.3°~30.1°
Min. Object Distance	0.5m
Focus control	Simple focus(Motorized V/F) / Manual, Remote control via network
Lens Type	DC auto iris, P iris
Mount Type	Board type
<b>Pan / Tilt / Rotate</b>	
Pan Range	0~350°
Tilt Range	0~67°
Rotate Range	0~355°
<b>Operational</b>	
IR Viewable Length	30m
Camera Title	Off / On (Displayed up to 20 characters per line) - W/W : English/Numeric/Special Characters - China : English/Numeric/Special/Chinese Characters - Common : Multi-line (Max 5), Color (Grey/Green/Red/Blue/Black/White), Transparency, Auto Scale by Resolution
Day & Night	True Day & Night
Backlight Compensation	Off / BLC
Wide Dynamic Range	120dB
Digital Noise Reduction	SSNR(Off / On)
Motion Detection	Off / On (4ea polygoon zones)
Privacy Masking	Off / On (6ea rectangler zones)
Gain Control	Off / Low / Middle / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
LDC(Lens distortion control)	On/Off (5 levels with Min/Max)
Electronic Shutter Speed	Minimum / Maximum / Anti flicker
Flip / Mirror	Flip / Mirror / Hallway view
Intelligent Video Analytics	Motion Detection with metadata, Tampering, Defocus
Alarm I/O	Input 1 / Output 1
Alarm Triggers	Motion detection, Tampering Detection, SD card error, NAS error, Alarm input, Defocus detection
Alarm Events	File upload via FTP and E-Mail Local storage recording at Event Notification via E-Mail External output
Pixel Counter	Support ( plug-in viewer only )

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.





## KES Co., Ltd.

C-3701, Simin-daero 365-40,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:  
KES-E1-16T0342  
Page (5) of (79)

<b>Network</b>	
Ethernet	RJ-45 (10/100BASE-T)
Video Compression Format	H.265, H.264, MJPEG
Resolution	2592x1520, 2560x1440(16:9) / 2304x1296 / 1920x1080 / 1280x1024 / 1280x960 / 1280x720 / 1024x768 / 800x600 / 800x450 / 720x576 / 720x480 / 640x480 / 640x360 / 320x240
Max. Framerate	H.265 : Max 20fps at 4M, Max 30fps at 2M all resolutions H.264 : Max 20fps at 4M, Max 30fps at 2M all resolutions MJPEG : Max 5fps
Smart codec	WiseStream
Video Quality Ajustment	H.265 : Target Bitrate Level Control H.264 : Target Bitrate Level Control MJPEG : Quality Level Control
Bitrate control method	H.265 : CBR or VBR H.264 : CBR or VBR MJPEG : VBR
Streaming Capability	Multiple Streaming(Up to 3 Profiles)
Audio I/O	Line in
Audio Compression Format	G.711 u-law /G.726 Selectable G.726(ADPCM) : 8KHz, G.711 : 8KHz G.726 : 16Kbps, 24Kbps, 32Kbps, 40Kbps
Audio Communication	Uni-directional
IP	IPv4, IPv6
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Security	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access Log 802.1X Authentication
Streaming Method	Unicast / Multicast
Max. User Access	6 users at Unicast Mode
Edge storage	Micro SD/SDHC/SDXC Max 128G, NAS - Motion images recorded in the SD memory card can be downloaded - Manual recording at Local PC
Application Programming Inte	ONVIF Profile S, G SUNAPI(HTTP API)
Webpage Language	English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Portuguese, Czech, Polish, Turkish, Dutch, Hungary, Greek
Web Viewer	Supported OS: Windows 7, 8, 10, Mac OS X 10.8. 10.9. 10.10. 10.11 [Non-plugin Webviewer] Supported Browser: Google Chrome 47, MS Edge 20 Support Codec : Video-H.264, MJPEG (Max. 1M 15fps), Audio-G.711 [Plug-in Webviewer] Supported Browser : MS Explore 11 , Mozilla Firefox 43, Apple Safari 9 * Mac OS X only
Central Management Software	SmartViewer

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



## KES Co., Ltd.

C-3701, Simin-daero 365-40,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:  
KES-E1-16T0342  
Page (6) of (79)

<b>Environmental</b>	
Operating Temperature / Hum	-30°C ~ +55°C / Less than 90% RH * Start up should be done at above -20°C
Storage Temperature / Humid	-30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH
Ingress Protection	IP66
Vandal Resistance	IK10
<b>Electrical</b>	
Input Voltage / Current	PoE(IEEE802.3af, Class3), DC 12V
Power Consumption	Max.7.2W(PoE), Max.6.4W(DC12V)
<b>Mechanical</b>	
Color / Material	Ivory / Metal
Dimension (WxHxD)	φ137x H106.1
Weight	690g

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



## 1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

Voltage  220 Vac  230 Vac  240 Vac  PoE  12 Vdc  
Frequency  50 Hz  60 Hz  Hz

## 1.2 Variant Model Differences

Not applicable

## 1.3 Device Modifications

Not applicable

## 1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	QNV-7080RP	-	Tianjin Samsung Techwin Opto-Electronic Co.,Ltd.	E.U.T

## 1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
NOTEBOOK	HP ProBook 4430s	CNU2084CVW	HP	-
NOTEBOOK Adapter	Series PPP00H	F12921201063695	CHICONY POWER TECHNOLOGY (SUZHOU) CO.,LTD,	-
PoE Adapter	RP-PEG048I	-	REPOTEC	-
Alarm Jig	-	-	-	-



## 1.6 External I/O Cabling

- DC 12 V Mode

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (E.U.T)	LAN(RJ-45)	NOTEBOOK	LAN(RJ-45)	5.0	U
	Alarm	Alarm	Alarm	3.0	U

- PoE Mode

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (E.U.T)	LAN(PoE)	PoE	LAN(PoE)	5.0	U
	Alarm	Alarm	Alarm	3.0	U
PoE	LAN(RJ-45)	NOTEBOOK	LAN(RJ-45)	4.0	U

\* Unshielded=U, Shielded=S

## 1.7 E.U.T Operating Mode(s)

Equipment under test was operated during the measurement under the following conditions:


Test mode	Normal operating
DC 12 V	MONITORING, PING TEST
PoE	MONITORING, PING TEST

- Input power condition during the measurements was 12 v (dc) , PoE


## 1.8 Configuration

■ AC Main  
 □ DC Main

- DC 12 V Mode



- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.







## 1.9 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

## 1.10 Test Facility

The measurement facility is located at 473-29 Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Korea. The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22.

## 1.11 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	<b>FCC</b>	3 & 10 meter Open Area Test Sites and one conducted site to perform FCC Part 15/18 measurements.	
JAPAN	<b>VCCI</b>	Mains Ports Conducted Interference Measurement, Telecommunication Ports Conducted Disturbance Measurement and Radiation 10 meter site, Facility for measuring radiated disturbance above 1 GHz	 R-4308, C-4798, T-2311, G-914
KOREA	<b>MSIP</b>	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
Canada	<b>IC</b>	3 & 10 meter Open Area Test Sites and one conducted site	 4769B-1
Europe	<b>CE</b>	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	
International	<b>KOLAS</b>	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	

## 2.0 Test Regulations

The emissions tests were performed according to following regulations:

**EMC – Directive 2014/30/EU**

EN 61000-6-3:2011

EN 61000-6-1:2007

EN 61000-6-4:2007 +A1:2011

EN 61000-6-2:2005

EN 55011:2007 +A1:2010

Group 1  
 Class A

Group 2  
 Class B

EN 55014-1:2006 +A2:2011

EN 55014-2:1997 +A2:2008

EN 55015:2013

EN 61547:2009

EN 55022:2010

Class A

Class B

EN 55024:2010 +A1:2015

EN 50130-4:2011 +A1:2014

EN 61000-3-2:2014

EN 61000-3-3:2013

EN 61326-1:2013



- 
- |   |                                  |                                  |
|---|----------------------------------|----------------------------------|
| <input type="checkbox"/> <b>VCCI V-3 / 2015.04</b>            | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input type="checkbox"/> <b>AS/NZS CISPR22:2009 +A1:2010</b>  | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input type="checkbox"/> <b>47 CFR Part 15, Subpart B</b>     |                                  |                                  |
| <input type="checkbox"/> CISPR 22:2009 +A1:2010               | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input type="checkbox"/> ANSI C63.4-2009                      |                                  |                                  |
| <input type="checkbox"/> <b>IC Regulation ICES-003 : 2016</b> |                                  |                                  |
| <input type="checkbox"/> CAN/CSA CISPR 22-10                  | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B |
| <input type="checkbox"/> ANSI C63.4-2014                      |                                  |                                  |
| <input type="checkbox"/> <b>RE- Directive 2014/53/EU</b>      |                                  |                                  |
| <input type="checkbox"/> EN 301 489-1 V1.9.2                  |                                  |                                  |
| <input type="checkbox"/> Equipment for fixed use              |                                  |                                  |
| <input type="checkbox"/> Equipment for vehicular use          |                                  |                                  |
| <input type="checkbox"/> Equipment for portable use           |                                  |                                  |
| <input type="checkbox"/> EN 301 489-3 V1.6.1                  |                                  |                                  |
| <input type="checkbox"/> EN 301 489-17 V2.2.1                 |                                  |                                  |
| <input type="checkbox"/> EN 60945:2002                        |                                  |                                  |

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



## 2.1 Conducted Emissions at Mains Power Ports

**Test Date**

N/A

**Test Location**

Electro wave Shieldroom

**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
<input type="checkbox"/>	EMI Test Receiver	ESR3	R&S	101783	05, 03, 2017
<input type="checkbox"/>	LISN	ENV216	R&S	101137	02, 04, 2017
<input type="checkbox"/>	LISN	ENV216	R&S	101786	05, 02, 2017
<input type="checkbox"/>	Electro wave Shieldroom	-	SEMITEC	-	-

**Test Conditions**Temperature: °C  
Relative Humidity: %**Frequency Range of Measurement**

150 kHz to 30 MHz

**Instrument Settings**

IF Band Width: 9 kHz

**Test Results**

The requirements are:

- PASS  
 NOT PASS  
 NOT APPLICABLE

**Remarks**

Because the E.U.T power is 12 V (dc) power and PoE, limits are not specified.

## 2.2 Conducted Emissions at Telecommunication Ports

### Test Date

Jul. 09, 2016

### Test Location

Electro wave Shieldroom

### Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
<input checked="" type="checkbox"/>	EMI Test Receiver	ESR3	R&S	101783	05, 03, 2017
<input checked="" type="checkbox"/>	LISN	ENV216	R&S	101137	02, 04, 2017
<input checked="" type="checkbox"/>	LISN	ENV216	R&S	101786	05, 02, 2017
<input checked="" type="checkbox"/>	8-Wire ISN CAT3	CAT3 8158	Schwarzbeck Mess	8158-0019	04, 01, 2017
<input checked="" type="checkbox"/>	8-Wire ISN CAT5	CAT5 8158	Schwarzbeck Mess	8158-0030	04, 01, 2017
<input type="checkbox"/>	8-Wire ISN CAT6	NTFM 8158	Schwarzbeck Mess	8158-0029	08, 14, 2016
<input checked="" type="checkbox"/>	Electro wave Shieldroom	-	SEMITEC	-	-

### Test Conditions

Temperature: 22,2 °C

Relative Humidity: 43,3 %

### Frequency Range of Measurement

150 kHz to 30 MHz

### Instrument Settings

IF Band Width: 9 kHz

### Test Results

The requirements are:

- PASS
- NOT PASS
- NOT APPLICABLE

### Remarks

See Appendix A for test data.



## 2.4 Radiated Electric Field Emissions(Above 1 GHz)

**Test Date**

Jul. 06, 2016

**Test Location**

Semi Anchoic Chamber #2

**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
<input checked="" type="checkbox"/>	EMI Test Receiver	ESU26	R&S	100552	04, 24, 2017
<input checked="" type="checkbox"/>	Broadband Coaxial Preamplifier	BBV 9718	Schwarzbeck Mess - Elektronik	9718-246	10, 23, 2016
<input checked="" type="checkbox"/>	DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H.SYSTEM,INC	781	05, 07, 2017
<input checked="" type="checkbox"/>	Semi Anchoic Chamber #2	-	SEMITEC	-	-
<input checked="" type="checkbox"/>	Antenna Mast	-	AUDIX	-	-
<input checked="" type="checkbox"/>	Turn Table	-	AUDIX	-	-

**Test Conditions**Temperature: 23,6 °C  
Relative Humidity: 50,3 %**Frequency Range of Measurement**

1 GHz to 6 GHz

**Instrument Settings**

IF Band Width: 1 MHz

**Test Results**

The requirements are:

- PASS  
 NOT PASS  
 NOT APPLICABLE

**Remarks**See Appendix A for test data.



## 2.5 Harmonic Current Emissions

### Test Date

N/A

### Test Location

Electro wave Shieldroom

### Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
<input type="checkbox"/>	AC Source	ACS 500 N	EM TEST	V1024106760	08, 13, 2016
<input type="checkbox"/>	Digital Power Analyzer	DPA 500 N	EM TEST	V1024106759	08, 13, 2016

### Test Conditions

Temperature: °C  
Relative Humidity: %

### Classification of Equipment for Harmonic Current Emissions

- Class A
- Class B
- Class C(Below 25 W)
- Class C(Above 25 W)
- Class D

### Test Results

The requirements are:

- PASS
- NOT PASS
- NOT APPLICABLE

### Remarks

N/A : Because the E.U.T power is less than 75 W, limits are not specified.





## 2.6 Voltage Fluctuations and Flicker

### Test Date

N/A

### Test Location

Electro wave Shieldroom

### Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
<input type="checkbox"/>	AC Source	ACS 500 N	EM test	V1024106760	08, 13, 2016
<input type="checkbox"/>	Digital Power Analyzer	DPA 500 N	EM test	V1024106759	08, 13, 2016

### Test Conditions

Temperature: °C  
Relative Humidity: %

### Test Results

The requirements are:

- PASS
- NOT PASS
- NOT APPLICABLE

### Remarks

N/A : Because the E.U.T power is 12 v (dc) power and PoE, limit are not specified.

### 3.0 Criteria for compliance

Criteria for compliance was based on the following guidelines:  
EN 50130-4:2011 +A1:2014 Alarm systems-Part 4: Electromagnetic compatibility Product family standard: Immunity requirements for components of fire, intruder and social alarm systems

The variety and the diversity of the apparatus within the scope of this document makes it difficult to define precise criteria for the evaluation of the immunity test results.

If as a result of the application of the tests defined in this standard, the apparatus becomes dangerous or unsafe then the apparatus shall be deemed to have failed the test.

A functional description and a definition of performance by the manufacture and noted in the test report, based on the following criteria:

#### Electrostatic discharge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing that is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change.

#### Radiated electromagnetic fields

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing which could be interpreted by associated equipment as a change, and no such

Flickering of indicators occurs at a field strength of 3 V/m.

For components of CCTV systems, where the picture is allowed at 10 V/m, providing.

(a) there is no permanent damage or change to EUT

(e.g. no corruption of memory or changes to programmable setting etc.)

(b) at 3 V/m, any deterioration of the picture is so minor that the system could still be used; and

(c) there is no observable deterioration of the picture at 1 V/m.

**Fast transient burst / slow high energy voltage surge**

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing

That there is no residual is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change.

**Conducted RF immunity**

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing

That there is no residual is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change, and no such flickering of indicators oeuvres at  $U = 130 \text{ dB}\mu\text{V}$ .

For component of CCTV systems, where the status is monitored by observing the TV picture, then deterioration of the picture is allowed at  $U = 140 \text{ dB}\mu\text{V}$ , providing:

- (a) there is no permanent damage or change to the EUT  
(e.g. no corruption of memory or changes to programmable settings etc.)
- (b) at  $U = 130 \text{ dB}\mu\text{V}$ , any deterioration of the picture is so minor that the system could still be used; and
- (c) there in no observable deterioration of the picture at  $U = 120 \text{ dB}\mu\text{V}$ .

**Voltage dip/interruption / Voltage variation**

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the conditioning is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change. The EUT shall meet the acceptance criteria for the functional test, after the conditioning.

### 3.1 Electrostatic Discharge

**Reference Standard**

EN 61000-4-2:2009

**Test Date**

Jul. 03, 2016

**Test Location**

EMS-ESD: Electro wave Shieldroom

**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
<input checked="" type="checkbox"/>	ESD SIMULATOR	ESS-2000	Noise Ken	ESS05X4620	02, 24, 2017
<input checked="" type="checkbox"/>	HCP	-	Noise Ken	-	-
<input checked="" type="checkbox"/>	VCP	-	Noise Ken	-	-

**Test Conditions**

Temperature: 21,9 °C  
Relative Humidity: 50,8 %  
Atmospheric Pressure: 99,1 kPa

**Test Specifications**

Discharge Factor: ≥ 1 s

Discharge Impedance: 330 ohm / 150 pF

Kind of Discharge: Air, Contact (direct and indirect)

Polarity: Positive and Negative

Number of Discharge: 10 at all locations for Air discharge  
10 at all locations for Contact discharge

Discharge Voltage:	Contact	Air	HCP	VCP
	<input type="checkbox"/> 2 kV	<input checked="" type="checkbox"/> 2 kV	<input type="checkbox"/> 2 kV	<input type="checkbox"/> 2 kV
	<input type="checkbox"/> 4 kV	<input checked="" type="checkbox"/> 4 kV	<input type="checkbox"/> 4 kV	<input type="checkbox"/> 4 kV
	<input checked="" type="checkbox"/> 6 kV	<input type="checkbox"/> 6 kV	<input checked="" type="checkbox"/> 6 kV	<input checked="" type="checkbox"/> 6 kV
	<input type="checkbox"/> 8 kV	<input checked="" type="checkbox"/> 8 kV	<input type="checkbox"/> 8 kV	<input type="checkbox"/> 8 kV
	<input type="checkbox"/> 15 kV	<input type="checkbox"/> 15 kV	<input type="checkbox"/> 15 kV	<input type="checkbox"/> 15 kV


Notes: HCP: Horizontal coupling plane  
VCP: Vertical coupling plane

Required Performance Criteria:  Complied

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

**Location of Discharge:**

- DC 12 V Mode



- DC 12 V Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



- PoE Mode



- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



### Test Data

- DC 12 V Mode

Indirect Discharge

No.	Test Point	Discharge Method	Performance	Remarks
			Observation	
1	HCP Contact	Contact Discharge	Complied	-
2	VCP Contact	Contact Discharge	Complied	-

Direct Discharge

No.	Test Point	Discharge Method	Performance	Remarks
			Observation	
1	Enclosure 1	Contact Discharge	Complied	-
2	Enclosure 2	Contact Discharge	Complied	-

- PoE Mode

Indirect Discharge

No.	Test Point	Discharge Method	Performance	Remarks
			Observation	
1	HCP Contact	Contact Discharge	Complied	-
2	VCP Contact	Contact Discharge	Complied	-

Direct Discharge

No.	Test Point	Discharge Method	Performance	Remarks
			Observation	
1	Enclosure 1	Contact Discharge	Complied	-
2	Enclosure 2	Contact Discharge	Complied	-

Note: "Blank" = Not performed

Observations:

Complied – No degradation of function

### Test Results

- PASS Required Performance Criteria
- NOT PASS Required Performance Criteria

### Remarks

PASS Required Performance Criteria.

## 3.2 Radiated Electric Field Immunity

### Reference Standard

EN 61000-4-3:2006 +A2:2010

### Test Date

Jul. 07, 2016

### Test Location

EMS-RS:  Semi Anchoic Chamber #1       Semi Anchoic Chamber #2

### Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
<input checked="" type="checkbox"/>	SIGNAL GENERATOR	SMB 100A	R&S	108252	08, 13, 2016
<input checked="" type="checkbox"/>	BROADBAND AMPLIFIER	BBA100	R&S	101239	08, 13, 2016
<input checked="" type="checkbox"/>	BROADBAND AMPLIFIER	100S1G6M1	AR	579931	08, 13, 2016
<input checked="" type="checkbox"/>	POWER METER	NRP2	R&S	103475	08, 13, 2016
<input checked="" type="checkbox"/>	AVG POWER SENSOR	NRP-Z91	R&S	102526	08, 13, 2016
<input checked="" type="checkbox"/>	AVG POWER SENSOR	NRP-Z91	R&S	102527	08, 13, 2016
<input checked="" type="checkbox"/>	Stacked Log.-Per.Antenna	STLP 9128 D	Schwarzbeck	9128D038	-
<input checked="" type="checkbox"/>	DIRECTIONAL COUPLER	KYDC-D1070-DX40	KyTelecom Co., Ltd.	KY150001	09, 25, 2016
<input checked="" type="checkbox"/>	Semi Anchoic Chamber #2		SEMITEC	-	-



**Test Conditions**

Temperature: 21,9 °C  
Relative Humidity: 48,6 %  
Atmospheric Pressure: 100,2 kPa

**Test Specifications**

Antenna Polarization: Horizontal & vertical unless indicated otherwise

Antenna Distance:  3 m

Field Strength:  1 V/m  3 V/m  
 10 V/m

Frequency Range:  80 MHz to 1 GHz  1,4 GHz to 2,7 GHz  
 80 MHz to 2,7 GHz

Modulation:  AM, 80 %, 1 kHz sine wave  
 PM, 1 Hz (0,5 s ON : 0,5 s OFF)

Frequency step:  1 % step

Dwell Time:  1 s  3 s

# of Sides Radiated:  4

Required Performance Criteria:  Complied

**Test Data**

- DC 12 V Mode

Side Exposed	Observation	
	Horizontal	Vertical
Front	Complied	Complied
Right	Complied	Complied
Back	Complied	Complied
Left	Complied	Complied



**KES Co., Ltd.**

C-3701, Simin-daero 365-40,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:  
KES-E1-16T0342  
Page (27) of (79)

- PoE Mode

Side Exposed	Observation	
	Horizontal	Vertical
Front	Complied	Complied
Right	Complied	Complied
Back	Complied	Complied
Left	Complied	Complied

Note: "Blank" = Not performed

Observations:  
Complied – No degradation of function

**Test Results**

- PASS Required Performance Criteria
- NOT PASS Required Performance Criteria

**Remarks**

PASS Required Performance Criteria.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



### 3.3 Electrical Fast Transients/Bursts

**Reference Standard**

EN 61000-4-4:2012

**Test Date**

Jul. 05, 2016

**Test Location**

EMS-EFT: Electro wave Shieldroom

**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
<input checked="" type="checkbox"/>	Ultra Compact Simulator	UCS 500 N5	EM TEST	V0936105120	06, 27, 2017
<input checked="" type="checkbox"/>	Capacitive Coupling Clamp	HFK	EM TEST	070925	06, 27, 2017
<input checked="" type="checkbox"/>	Motor Variac	MV2616	EM TEST	V0936105123	06, 27, 2017

**Test Conditions**

Temperature: 22,4 °C  
Relative Humidity: 54,3 %  
Atmospheric Pressure: 99,6 kPa

**Test Specifications**

Pulse Amplitude & Polarity:  
(AC Power Lines)  ± 1.0 kV  ± 2.0 kV  
 ± 4.0 kV

Pulse Amplitude & Polarity:  
(Other supply / Signal Lines)  ± 0.5 kV  ± 1.0 kV  
 ± 2.0 kV

Burst Period:  300 ms  2 s

Repetition Rate:  5 klz  100 klz

Duration of Test Voltage:  ≥ 1 min

Required Performance Criteria:  Complied

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

**Test Data**

- DC 12 V Mode

Input a.c. power ports – Coupling/Decoupling Network used

Mode of Application	OBSERVATIONS	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

Input d.c. power ports – Coupling/Decoupling Network used

Mode of Application	OBSERVATIONS	
	(+) Burst (kV)	(-) Burst (kV)
L1 – L2	Complied	Complied

Signal ports and telecommunication ports – Coupling Clamp used

Mode of Application	OBSERVATIONS	
	(+) Burst (kV)	(-) Burst (kV)
RJ-45 (LAN)	Complied	Complied
Alarm	Complied	Complied

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



- PoE Mode

Input a.c. power ports – Coupling/Decoupling Network used

Mode of Application	OBSERVATIONS	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

Input d.c. power ports – Coupling/Decoupling Network used

Mode of Application	OBSERVATIONS	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

Signal ports and telecommunication ports – Coupling Clamp used

Mode of Application	OBSERVATIONS	
	(+) Burst (kV)	(-) Burst (kV)
RJ-45 (PoE)	Complied	Complied
Alarm	Complied	Complied

Note: "Blank" = Not performed

Observations:  
Complied – No degradation of function

**Test Results**

- PASS Required Performance Criteria
- NOT PASS Required Performance Criteria

**Remarks**

PASS Required Performance Criteria.

### 3.4 Surge Transients

**Reference Standard**

EN 61000-4-5:2014

**Test Date**

Jul. 05, 2016

**Test Location**

EMS-Surge: Electro wave Shieldroom

**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
<input checked="" type="checkbox"/>	Ultra Compact Simulator	UCS 500 N5	EM TEST	V0936105120	06, 27, 2017
<input checked="" type="checkbox"/>	MotorVariac	MV2616	EM TEST	V0936105123	06, 27, 2017
<input type="checkbox"/>	CDN	CNV 508T5	EM TEST	P1549168422	04, 27, 2017
<input checked="" type="checkbox"/>	CDN	CNV 508N1	EM TEST	P1551168979	04, 27, 2017

**Test Conditions**

Temperature: 22,4 °C  
Relative Humidity: 54,3 %  
Atmospheric Pressure: 99,6 kPa

**Test Specifications**

**AC Power Lines**

Source Impedance: 12 ohm for common mode and 2 ohm for differential mode

Surge Amplitude :  
Common Mode  
 (0,5 / 1,0 / 2,0) kV  
Differential Mode  
 (0,5 / 1,0) kV

Number of Surges:  5 surges per angle

Angle:  0°, 90°, 180°, 270° (input a.c. power port)

Polarity:  Positive & Negative

Repetition Rate:  1 surge per min  1 surge per 30 sec.

Required Performance Criteria:  Complied



**Other supply / Signal Lines**

Source Impedance: 42 ohm for common mode  
Surge Amplitude: Common Mode  
 (0,5 / 1,0) kV  
  
Number of Surges:  5 Surges  
  
Polarity:  Positive & Negative  
  
Repetition Rate:  1 surge per min     1 surge per 30 sec.  
  
Required Performance Criteria:  Complied

**Test Data**

- DC 12 V Mode

Line to Line – Differential Mode

Mode of Application	OBSERVATIONS	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-

Line to Earth – Common Mode

Mode of Application	OBSERVATIONS	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-

**Signal Lines**

Line to Earth – Common Mode

Mode of Application	OBSERVATIONS	
	(+) Surge (kV)	(-) Surge (kV)
RJ-45 (LAN)	Complied	Complied
Alarm	Complied	Complied



- PoE Mode

Line to Line – Differential Mode

Mode of Application	OBSERVATIONS	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-

Line to Earth – Common Mode

Mode of Application	OBSERVATIONS	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-

**Signal Lines**

Line to Earth – Common Mode

Mode of Application	OBSERVATIONS	
	(+) Surge (kV)	(-) Surge (kV)
RJ-45 (PoE)	Complied	Complied
Alarm	Complied	Complied

Note: "Blank" = Not performed

Observations:  
Complied – No degradation of function

**Test Results**

- PASS Required Performance Criteria
- NOT PASS Required Performance Criteria

**Remarks**

PASS Required Performance Criteria.

### 3.5 Conducted Disturbance

**Reference Standard**

EN 61000-4-6:2014

**Test Date**

Jul. 04, 2016

**Test Location**

EMS-CS: Electro wave Shieldroom

**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
<input checked="" type="checkbox"/>	Continuous Wave Generator	CWS 500N1	EM TEST	V0936105119	09, 25, 2016
<input checked="" type="checkbox"/>	6 dB Attenuator	ATT6	EM TEST	1208-34	08, 13, 2016
<input checked="" type="checkbox"/>	CDN	CDN-M2/M3N	EM TEST	0909-06	08, 13, 2016
<input checked="" type="checkbox"/>	EM Injection Clamp	EM 101	Liithi	35943	02, 04, 2017

**Test Conditions**

Temperature: 23,3 °C  
Relative Humidity: 58,2 %  
Atmospheric Pressure: 99,2 kPa

**Test Specifications**

Frequency range:  150 kHz to 100 MHz  10 kHz to 30 MHz  
 150 kHz to 230 MHz  10 kHz to 100 MHz

Voltage Level:  1 Vrms  3 Vrms  
 10 Vrms

Modulation:  AM, 80 %, 1 kHz sine wave  
 PM, 1 Hz (0,5 s ON : 0,5 s OFF)

Frequency step:  1 % step

Dwell Time:  1 s  3 s

Required Performance Criteria:  Complied



**Test Data**

- DC 12 V Mode

Input a.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observation
-	CDN ( <input type="checkbox"/> M2, <input type="checkbox"/> M3)	-

Input d.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observation
L1 - L2	CDN ( <input checked="" type="checkbox"/> M2, <input type="checkbox"/> M3)	Complied

Signal ports and telecommunication ports

Coupling Location (Line Stressed)	Coupling Method	Observation
RJ-45 (LAN)	EM Injection Clamp	Complied
Alarm	EM Injection Clamp	Complied

- PoE Mode

Input a.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observation
-	CDN ( <input type="checkbox"/> M2, <input type="checkbox"/> M3)	-

Input d.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observation
-	CDN ( <input type="checkbox"/> M2, <input type="checkbox"/> M3)	-

Signal ports and telecommunication ports

Coupling Location (Line Stressed)	Coupling Method	Observation
RJ-45 (PoE)	EM Injection Clamp	Complied
Alarm	EM Injection Clamp	Complied

Notes: CDN = Coupling Decoupling Network  
 "blank" = Not performed

Observations:  
 Complied - No degradation of function

**Test Results**

- PASS Required Performance Criteria
- NOT PASS Required Performance Criteria

**Remarks**

PASS Required Performance Criteria.



### 3.6 Voltage Dips and Short Interruptions

**Reference Standard**

EN 61000-4-11:2004

**Test Date**

N/A

**Test Location**

EMS-Voltage dip: Electro wave Shieldroom

**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
<input type="checkbox"/>	Transient Test System	TRA3000F-S-D-V	EMC PARTNER AG	1524	03, 25, 2017
<input type="checkbox"/>	MotorVariac	VAR-EXT1000	EMC PARTNER AG	1507	03, 25, 2017

**Test Conditions**

Temperature: °C  
Relative Humidity: %  
Atmospheric Pressure: kPa



---

### Test Specifications & Observations/Remarks

<u>Test Level</u>	<u>Duration [in period/ms (50 Hz)]</u>	<u>Results</u>
<input type="checkbox"/> 20 % dip	<input type="checkbox"/> 250 /5000	_____
<input type="checkbox"/> 30 % dip	<input type="checkbox"/> 25 /500	_____
<input type="checkbox"/> 60 % dip	<input type="checkbox"/> 10 /200	_____
<input type="checkbox"/> 100 % dip	<input type="checkbox"/> 250 /5000	_____
<b>- Voltage variations</b>		
<input type="checkbox"/> Unom + 10 %	<input type="checkbox"/> 253 V (ac)	_____
<input type="checkbox"/> Unom - 15 %	<input type="checkbox"/> 195.5 V (ac)	_____

Observations:  
Complied – No degradation of function

#### Test Results

- PASS Required Performance Criteria
- NOT PASS Required Performance Criteria
- NOT APPLICABLE

#### Remarks

N/A : Because the E.U.T power is 12 v (dc) power and PoE, limits are not specified.



**KES Co., Ltd.**

C-3701, Simin-daero 365-40,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:  
KES-E1-16T0342  
Page (38) of (79)

---

## **APPENDIX A – TEST DATA**

### **Conducted Emissions at Mains Power Ports**

**[HOT]**

**N/A**

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



**KES Co., Ltd.**

C-3701, Simin-daero 365-40,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:  
KES-E1-16T0342  
Page (39) of (79)

---

**[NEUTRAL]**

**N/A**

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


## Conducted Emissions at Telecommunication Ports

- DC 12 V Mode

[10 Mbps]

### Common Information

Test Description:	Telecommunication Emission
Model No.:	QNV-7080RP
Mode	DC 12 V_10 Mbps
Operator Name:	KES



### Final Result


Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.470000	--	50.57	74.51	23.94	1000.0	9.000	Single Line	10.0
0.470000	58.20	--	87.51	29.31	1000.0	9.000	Single Line	10.0
4.975000	--	43.60	74.00	30.40	1000.0	9.000	Single Line	9.9
4.975000	52.93	--	87.00	34.07	1000.0	9.000	Single Line	9.9
5.100000	--	43.21	74.00	30.79	1000.0	9.000	Single Line	9.9
5.100000	52.64	--	87.00	34.36	1000.0	9.000	Single Line	9.9
9.990000	--	45.15	74.00	28.85	1000.0	9.000	Single Line	10.1
9.990000	54.85	--	87.00	32.15	1000.0	9.000	Single Line	10.1
16.490000	--	50.83	74.00	23.17	1000.0	9.000	Single Line	10.1
16.490000	55.18	--	87.00	31.82	1000.0	9.000	Single Line	10.1

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

**[100 Mbps]**

**Common Information**

Test Description:	Telecommunication Emission
Model No.:	QNV-7080RP
Mode	DC 12 V_100 Mbps
Operator Name:	KES



**Final Result**

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.160000	--	57.68	83.46	25.78	1000.0	9.000	Single Line	9.6
0.160000	67.22	--	96.46	29.24	1000.0	9.000	Single Line	9.6
0.460000	--	49.83	74.69	24.86	1000.0	9.000	Single Line	9.5
0.460000	57.58	--	87.69	30.11	1000.0	9.000	Single Line	9.5
2.360000	--	40.37	74.00	33.63	1000.0	9.000	Single Line	9.3
2.360000	50.12	--	87.00	36.88	1000.0	9.000	Single Line	9.3
16.745000	--	50.66	74.00	23.34	1000.0	9.000	Single Line	9.6
16.745000	54.84	--	87.00	32.16	1000.0	9.000	Single Line	9.6
17.160000	--	50.38	74.00	23.62	1000.0	9.000	Single Line	9.5
17.160000	54.23	--	87.00	32.77	1000.0	9.000	Single Line	9.5


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

- PoE Mode

**[10 Mbps]**

### Common Information

Test Description:	Telecommunication Emission
Model No.:	QNV-7080RP
Mode	PoE_10 Mbps
Operator Name:	KES



### Final\_Result

Frequency (MHz)	QuasiPeak (dBm)	CAverage (dBm)	Limit (dBm)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.660000	--	56.74	74.00	17.26	1000.0	9.000	Single Line	9.9
0.660000	58.58	--	87.00	28.42	1000.0	9.000	Single Line	9.9
2.205000	--	57.75	74.00	16.25	1000.0	9.000	Single Line	9.8
2.205000	58.15	--	87.00	28.85	1000.0	9.000	Single Line	9.8
4.995000	--	37.98	74.00	36.02	1000.0	9.000	Single Line	9.9
4.995000	53.19	--	87.00	33.81	1000.0	9.000	Single Line	9.9
5.730000	--	54.05	74.00	19.95	1000.0	9.000	Single Line	9.9
5.730000	56.44	--	87.00	30.56	1000.0	9.000	Single Line	9.9
10.010000	--	39.31	74.00	34.69	1000.0	9.000	Single Line	10.1
10.010000	56.94	--	87.00	30.06	1000.0	9.000	Single Line	10.1


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



**[100 Mbps]**

**Common Information**

Test Description:	Telecommunication Emission
Model No.:	QNV-7080RP
Mode	PoE_100 Mbps
Operator Name:	KES



**Final\_Result**

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.565000	--	48.94	74.00	25.06	1000.0	9.000	Single Line	9.5
0.565000	56.20	--	87.00	30.80	1000.0	9.000	Single Line	9.5
0.660000	--	56.25	74.00	17.75	1000.0	9.000	Single Line	9.4
0.660000	58.13	--	87.00	28.87	1000.0	9.000	Single Line	9.4
1.320000	--	56.81	74.00	17.19	1000.0	9.000	Single Line	9.3
1.320000	57.49	--	87.00	29.51	1000.0	9.000	Single Line	9.3
2.205000	--	56.14	74.00	17.86	1000.0	9.000	Single Line	9.3
2.205000	56.50	--	87.00	30.50	1000.0	9.000	Single Line	9.3
5.730000	--	53.39	74.00	20.61	1000.0	9.000	Single Line	9.4
5.730000	54.13	--	87.00	32.87	1000.0	9.000	Single Line	9.4

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

## Radiated Electric Field Emissions(Below 1 GHz)

- DC 12 V Mode

Frequency [MHz]	Amplitude [dB $\mu$ V]	ANT Polar. (H/V)	ANT. Height [m]	Correction Factor		Corrected Amplitude [dB $\mu$ V/m]	Applicable Limit [dB $\mu$ V/m]	Margin [dB]
				ANT. [dB/m]	Cable [dB]			
50.24	11.28	V	1.00	13.92	1.46	26.66	40.00	13.34
148.49	18.07	V	1.00	8.15	2.76	28.98	40.00	11.02
264.69	14.60	V	1.10	12.69	3.92	31.21	47.00	15.79
312.20	14.16	H	4.00	13.66	4.32	32.14	47.00	14.86
360.57	14.15	H	3.90	14.79	4.74	33.68	47.00	13.32
465.73	10.18	H	3.50	16.62	5.51	32.31	47.00	14.69

\* H : Horizontal, V : Vertical


- PoE Mode

Frequency [MHz]	Amplitude [dB $\mu$ V]	ANT Polar. (H/V)	ANT. Height [m]	Correction Factor		Corrected Amplitude [dB $\mu$ V/m]	Applicable Limit [dB $\mu$ V/m]	Margin [dB]
				ANT. [dB/m]	Cable [dB]			
49.35	15.28	V	1.00	13.92	1.45	30.65	40.00	9.35
126.00	15.64	H	4.00	9.12	2.54	27.30	40.00	12.70
149.25	17.72	V	1.00	8.17	2.77	28.66	40.00	11.34
230.54	14.21	V	1.00	11.98	3.59	29.78	47.00	17.22
312.16	13.80	H	3.90	13.66	4.32	31.78	47.00	15.22
456.72	12.24	H	4.00	16.49	5.44	34.17	47.00	12.83

\* H : Horizontal, V : Vertical

## Radiated Electric Field Emissions(Above 1 GHz)


- DC 12 V Mode



Site : chamber  
 Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) horizontal  
 : RBW:1000.000kHz VBW:1000.000kHz SWT:Auto  
 Project : NETWORK CAMERA  
 Model : QNV-7080RP  
 Mode : DC 12 V  
 Memo : 1 ~ 3 GHz

	Read Freq	Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	1248.00	36.55	24.89	7.23	40.00	300	56.00	-27.33	horizontal	Average
2	1248.00	50.83	24.89	7.23	40.00	300	76.00	-33.05	horizontal	Peak
3	1336.00	39.53	25.24	7.48	39.96	34	56.00	-23.71	horizontal	Average
4	1336.00	47.84	25.24	7.48	39.96	34	76.00	-35.40	horizontal	Peak
5 pp	1634.00	38.82	26.43	8.34	39.81	179	56.00	-22.22	horizontal	Average
6	1634.00	46.25	26.43	8.34	39.81	179	76.00	-34.79	horizontal	Peak
7	1998.00	28.05	27.87	9.34	39.63	210	56.00	-30.37	horizontal	Average
8	1998.00	43.84	27.87	9.34	39.63	210	76.00	-34.58	horizontal	Peak
9	2462.00	25.57	29.01	10.06	39.90	306	56.00	-31.26	horizontal	Average
10	2462.00	46.31	29.01	10.06	39.90	306	76.00	-30.52	horizontal	Peak
11	2598.00	27.03	29.35	10.27	39.98	228	56.00	-29.33	horizontal	Average
12 pk	2598.00	49.04	29.35	10.27	39.98	228	76.00	-27.32	horizontal	Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.




Site : chamber  
 Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) vertical  
 : RBW:1000.000kHz VBW:1000.000kHz SWT:Auto  
 Project : NETWORK CAMERA  
 Model : QNV-7080RP  
 Mode : DC 12 V  
 Memo : 1 ~ 3 GHz

	Read Freq	Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	1246.00	40.11	24.89	7.22	40.00	198	56.00	-23.78	vertical	Average
2	1246.00	54.09	24.89	7.22	40.00	198	76.00	-29.80	vertical	Peak
3 pp	1634.00	41.31	26.43	8.34	39.81	198	56.00	-19.73	vertical	Average
4	1634.00	47.88	26.43	8.34	39.81	198	76.00	-33.16	vertical	Peak
5	1992.00	30.78	27.85	9.33	39.63	331	56.00	-27.67	vertical	Average
6	1992.00	49.23	27.85	9.33	39.63	331	76.00	-29.22	vertical	Peak
7	2462.00	25.17	29.01	10.06	39.90	22	56.00	-31.66	vertical	Average
8	2462.00	41.66	29.01	10.06	39.90	22	76.00	-35.17	vertical	Peak
9	2598.00	29.17	29.35	10.27	39.98	242	56.00	-27.19	vertical	Average
10 pk	2598.00	52.52	29.35	10.27	39.98	242	76.00	-23.84	vertical	Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.






Site : chamber  
 Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) horizontal  
 : RBW:1000.000kHz VBW:1000.000kHz SWT:Auto  
 Project : NETWORK CAMERA  
 Model : QNV-7080RP  
 Mode : DC 12 V  
 Memo : 3 ~ 6 GHz

	Read Freq	Ant Level	Cable Factor	Preamp Loss	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	deg	dBuV/m	dB		
1	3747.00	26.37	31.58	13.00	40.36	124	60.00	-29.41	horizontal Average
2	3747.00	41.58	31.58	13.00	40.36	124	80.00	-34.20	horizontal Peak
3	4314.00	24.63	33.80	14.09	40.41	196	60.00	-27.89	horizontal Average
4	4314.00	37.58	33.80	14.09	40.41	196	80.00	-34.94	horizontal Peak
5 pp	4995.00	25.17	37.69	15.32	40.41	116	60.00	-22.23	horizontal Average
6 pk	4995.00	40.11	37.69	15.32	40.41	116	80.00	-27.29	horizontal Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.




Site : chamber  
 Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) vertical  
 : RBW:1000.000kHz VBW:1000.000kHz SWT:Auto  
 Project : NETWORK CAMERA  
 Model : QNV-7080RP  
 Mode : DC 12 V  
 Memo : 3 ~ 6 GHz

	Read Freq	Ant Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	3738.00	26.47	31.57	12.99	40.36	88	60.00	-29.33	vertical	Average
2	3738.00	42.18	31.57	12.99	40.36	88	80.00	-33.62	vertical	Peak
3	3789.00	25.69	31.66	13.09	40.37	97	60.00	-29.93	vertical	Average
4	3789.00	41.08	31.66	13.09	40.37	97	80.00	-34.54	vertical	Peak
5	4872.00	24.18	36.99	15.10	40.41	279	60.00	-24.14	vertical	Average
6	4872.00	36.58	36.99	15.10	40.41	279	80.00	-31.74	vertical	Peak
7 pp	4998.00	25.34	37.71	15.33	40.41	268	60.00	-22.03	vertical	Average
8 pk	4998.00	40.53	37.71	15.33	40.41	268	80.00	-26.84	vertical	Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

- PoE Mode



Site : chamber  
 Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) horizontal  
 : RBW:1000.000kHz VBW:1000.000kHz SWT:Auto  
 Project : NETWORK CAMERA  
 Model : QNV-7080RP  
 Mode : PoE  
 Memo : 1 ~ 3 GHz

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1 pp	1248.00	38.04	24.89	7.23	40.00	298	56.00	-25.84	horizontal	Average
2	1248.00	52.14	24.89	7.23	40.00	298	76.00	-31.74	horizontal	Peak
3	1484.00	28.95	25.83	7.91	39.88	171	56.00	-33.19	horizontal	Average
4	1484.00	42.65	25.83	7.91	39.88	171	76.00	-39.49	horizontal	Peak
5	1842.00	29.05	27.25	8.92	39.71	235	56.00	-30.49	horizontal	Average
6	1842.00	45.06	27.25	8.92	39.71	235	76.00	-34.48	horizontal	Peak
7	1962.00	28.59	27.73	9.25	39.65	237	56.00	-30.08	horizontal	Average
8	1962.00	45.01	27.73	9.25	39.65	237	76.00	-33.66	horizontal	Peak
9	2596.00	27.78	29.34	10.26	39.98	229	56.00	-28.60	horizontal	Average
10 pk	2596.00	49.55	29.34	10.26	39.98	229	76.00	-26.83	horizontal	Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.






**KES Co., Ltd.**

C-3701, Simin-daero 365-40,  
 Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
 Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
 www.kes.co.kr

Test report No.:  
 KES-E1-16T0342  
 Page (50) of (79)



Site : chamber  
 Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) vertical  
 : RBW:1000.000kHz VBW:1000.000kHz SWT:Auto  
 Project : NETWORK CAMERA  
 Model : QNV-7080RP  
 Mode : PoE  
 Memo : 1 ~ 3 GHz

	Read Freq	Ant Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1 pp	1336.00	40.92	25.24	7.48	39.96	351	56.00	-22.32	vertical	Average
2	1336.00	46.87	25.24	7.48	39.96	351	76.00	-36.37	vertical	Peak
3	1836.00	29.68	27.23	8.90	39.71	131	56.00	-29.90	vertical	Average
4	1836.00	47.61	27.23	8.90	39.71	131	76.00	-31.97	vertical	Peak
5	1998.00	32.80	27.87	9.34	39.63	32	56.00	-25.62	vertical	Average
6	1998.00	51.52	27.87	9.34	39.63	32	76.00	-26.90	vertical	Peak
7	2162.00	30.00	28.28	9.60	39.72	24	56.00	-27.84	vertical	Average
8	2162.00	50.91	28.28	9.60	39.72	24	76.00	-26.93	vertical	Peak
9	2598.00	28.89	29.35	10.27	39.98	241	56.00	-27.47	vertical	Average
10 pk	2598.00	52.31	29.35	10.27	39.98	241	76.00	-24.05	vertical	Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.






**KES Co., Ltd.**

C-3701, Simin-daero 365-40,  
 Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
 Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
 www.kes.co.kr


Test report No.:  
 KES-E1-16T0342  
 Page (51) of (79)



Site : chamber  
 Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) horizontal  
 : RBW:1000.000kHz VBW:1000.000kHz SWT:Auto  
 Project : NETWORK CAMERA  
 Model : QNV-7080RP  
 Mode : PoE  
 Memo : 3 ~ 6 GHz

	Read	Ant	Cable	Preamp	TPos	Limit	Over		
Freq	Level	Factor	Loss	Factor	deg	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	4518.00	24.71	34.97	14.46	40.41	292	60.00	-26.27	horizontal Average
2	4518.00	37.28	34.97	14.46	40.41	292	80.00	-33.70	horizontal Peak
3	4758.00	24.33	36.34	14.89	40.41	181	60.00	-24.85	horizontal Average
4	4758.00	38.18	36.34	14.89	40.41	181	80.00	-31.00	horizontal Peak
5 pp	4983.00	24.37	37.62	15.30	40.41	118	60.00	-23.12	horizontal Average
6 pk	4983.00	38.91	37.62	15.30	40.41	118	80.00	-28.58	horizontal Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Site : chamber  
 Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) vertical  
 : RBW:1000.000kHz VBW:1000.000kHz SWT:Auto  
 Project : NETWORK CAMERA  
 Model : QNV-7080RP  
 Mode : PoE  
 Memo : 3 ~ 6 GHz

	Read Freq	Ant Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	3744.00	27.69	31.58	13.00	40.36	86	60.00	-28.09	vertical	Average
2	3744.00	43.00	31.58	13.00	40.36	86	80.00	-32.78	vertical	Peak
3	4683.00	24.53	35.91	14.76	40.41	198	60.00	-25.21	vertical	Average
4	4683.00	37.02	35.91	14.76	40.41	198	80.00	-32.72	vertical	Peak
5	4872.00	24.17	36.99	15.10	40.41	109	60.00	-24.15	vertical	Average
6	4872.00	37.27	36.99	15.10	40.41	109	80.00	-31.05	vertical	Peak
7 pp	4989.00	24.54	37.66	15.31	40.41	95	60.00	-22.90	vertical	Average
8 pk	4989.00	39.36	37.66	15.31	40.41	95	80.00	-28.08	vertical	Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



## Harmonic Current Emissions and Voltage Fluctuations and Flicker

### Average harmonic current results

Hn	I <sub>eff</sub> [A]	% of Limit	Limit [A]	Result
1	N/A			
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				
17				
18				
19				
20				
21				
22				
23				
24				
25				
26				
27				
28				
29				
30				
31				
32				
33				
34				
35				
36				
37				
38				
39				
40				

Harmonic currents less than 0.6% of the input current measured under the test conditions, or less than 5 mA, whichever is greater, are disregarded.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Test Data - Harmonics (continued)

**Maximum harmonic current results**

Hn	I <sub>eff</sub> [A]	% of Limit	Limit [A]	Result
1	N/A			
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				
17				
18				
19				
20				
21				
22				
23				
24				
25				
26				
27				
28				
29				
30				
31				
32				
33				
34				
35				
36				
37				
38				
39				
40				

Harmonic currents less than 0.6% of the input current measured under the test conditions, or less than 5 mA, whichever is greater, are disregarded.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Test Data - Voltage Fluctuations

**Maximum Flicker results**

	<b>EUT values</b>	<b>Limit</b>	<b>Result</b>
Pst	N/A		
Plt			
dc [%]			
dmax [%]			
Tmax [s]			

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



**KES Co., Ltd.**

C-3701, Simin-daero 365-40,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:  
KES-E1-16T0342  
Page (56) of (79)

---

## **Test Setup Photos and Configuration**

### **Conducted Voltage Emissions**


N/A

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

## Conducted Telecommunication Emissions


- DC 12 V Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



## Radiated Electric Field Emissions(Below 1 GHz)

- DC 12 V Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

## Radiated Electric Field Emissions(Above 1 GHz)

- DC 12 V Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



**KES Co., Ltd.**

C-3701, Simin-daero 365-40,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:  
KES-E1-16T0342  
Page (63) of (79)

---

## Harmonic Current Emissions and Voltage Fluctuations and Flicker

N/A

---


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

## Electrostatic Discharge

- DC 12 V Mode



- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

## Radiated Electric Field Immunity

- DC 12 V Mode



- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.




## Electrical Fast Transients/Bursts

- DC 12 V Mode



- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.




## Surge Transients

- DC 12 V Mode



- PoE Mode




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

## Conducted Disturbance

- DC 12 V Mode



- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



**KES Co., Ltd.**

C-3701, Simin-daero 365-40,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:  
KES-E1-16T0342  
Page (69) of (79)

---

## **Voltage Dips and Short Interruptions**

N/A

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

## EUT External Photographs

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

---

## EUT Internal Photographs

(Internal View)



---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.




---

## EUT Internal View – Main Board

(Top)



(Bottom)



---


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

## EUT Internal View – Sub Board

(Top)



(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

---

## EUT Internal View – Lens Board

(Top)



(Bottom)



---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.





## Label and Location



### **NETWORK CAMERA**

Model No : QNV-7080RP

Manufacturer : Tianjin Samsung Techwin Opto-Electronic Co.,Ltd.

Made in of China

