



Model NO.	LICG30TV100B	LICG30TV100A	LICG30TV130V	LICG30TV130S	LICG30THC130J	LICG30THC200P	LICG30THC200V	LICG30THC200NA	LICG30THC200NS	LICG30THC200FV	LICG30THC200EP	LICG30THC200ES	LICG30THC200ESL	LICG30THC2003XEP	LICG30THC2003XES	LICG30THC2003XESL	LICG30TA200S	LICG30THC300A
Video Output Mode	TVI	TVI / CVBS	TVI / CVBS	TVI / CVBS	AHD / CVI /TVI / CVBS	AHD / CVI /TVI / CVBS	AHD / CVI /TVI / CVBS	AHD / CVI /TVI / CVBS	AHD / CVI /TVI / CVBS	AHD / CVI /TVI / CVBS	AHD / CVI /TVI / CVBS	AHD / CVI /TVI / CVBS	AHD / CVI /TVI / CVBS	AHD / CVI /TVI / CVBS	AHD / CVI /TVI / CVBS	AHD / CVI /TVI / CVBS	TVI /AHD / CVBS	AHD / CVI /TVI / CVBS

Image Sensor	OV9732	AR0141	OV9750	IMX225	S3130	P55220	OV2710	AR0237	IMX323	OV2718	MN34227	IMX323	IMX290	MN34227	IMX323	IMX290	IMX322	AR0330
DSP	HTC960	HTC960	HTC960	HTC960	HTC960E	HTC1080	HTC1080	NVP2441H	NVP2441H	HTC1080E	HTC1088	HTC1088	HTC1088	HTC1088	HTC1088	HTC1088	NVP2440H	HTC1080E
Image Resolution	720P	720P / 960H	960P / 960H	960P / 960H	960P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	1080P / 960H	TVI 3M ; AHD/ CVI 1080P; CVBS 960H;
Effective Pixels	1280*720	1280*720	1280*960	1280*960	1280*960	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080	1920*1536
TV System	PAL/NTSC																	
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s																	
S/N Ratio	≥50dB																	
Scanning System	Progressive Scan																	

[illegible]

Infrared LED	14μ x 24PCS
Infrared Distance	25M
IR Status	Under 10 Lux by CDS
IR Power On	CDS Auto Control

[illegible]

Housing	Metal, IP66
Bracket	YES
Dual Voltage	NO
IR Cut Filter	YES
Heater	NO
Operation Temperature	-10℃ ~ +50℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	196 (W) x 89 (H) x 75 (D) mm
Weight	880g